

## L-SD2510

### Diode for arrays of photovoltaic solar panels. Maximum current 2A

This device is planned to facilitate designers and installers of photovoltaic systems, in mounting the diode which stops the recirculation current, on strings of solar panels. In fact, being galvanically insulated, it allows not to mount the IP20 protection nor insulate the body.

The adapter makes the DIN rail mounting quickly and safely.

The working voltage allows its use for equipments according to the IEC 60364-7-712 standards.

### FEATURES

- Electrical insulation for DIN rail mounting
- High reverse blocking voltage
- Good thermal dissipation
- Galvanic isolation 3750Vac for 5 sec.
- Section of terminals 6 mm<sup>2</sup>



Symbols	Parameters	Conditions	L-SD2510-A	L-SD2510-B	Units
$V_L$	Max Working DC Voltage (IEC60364-7-712)	150 °C - 5 mA	500	1000	V
$V_{rrm}$	Max reverse Voltage (IEC60364-7-712)	$T_j$ 175°C	1000	2000	V
$V_f$	Max forward voltage drop for diode	$I_f = 10A$	0,82	1,58	V
$I_{avg}$	Maximum Average current for diode	DC Conduction	2 @ 85	2 @ 85	A @ °C
$I_{fsm}$	Max non repetitive surge current	10ms- $V_r=0$	383	383	A
$I^2t$	Max. fusing capability	10ms- $V_r=0$	733	733	A2s
$T_j(max)$	Max. operating junction temperature		175	175	°C
$T_{c-max}$	Max case temperature	DC Conduction (single)	90	90	°C
$T_c$	Max heatsink temperature	At 40°C room temperature	66	83	°C
	Dimensions (L x W x H)		10x20x77	10x20x77	mm
W	Weight		50	50	g

*Last verify of electrical parameters made on January 15, 2010.*

WARNING: Agentech srl reserves the right to change features and dimensions without prior notice.